

## Material Safety Data Sheet

### RESIN BONDED CUTTING AND GRINDING WHEELS

#### SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

1. PRODUCT NAME  
RESIN BONDED CUTTING AND GRINDING WHEELS
2. TRADE NAME  
SWORDS
3. HS CODE : 6804 22 00
4. MANUFACTURER

**Abrasives Technology Industries (ATI).**  
**BLDG 3561 UNIT NO.1, 2<sup>ND</sup> INDUSTRIAL AREA**  
**DAMMAM 34332-7592**

**Kingdom of Saudi Arabia**

Technical and Emergency Phone No:+966-559222774

REVISION DATE and No : AUGUST 2013 and 00

#### SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE DESCRIPTION	PERCENT	CAS#
Aluminum Oxide, Non-fibrous	70.000- 85.000	1344-28-1
Cured Phenol Formaldehyde Resin	8.000- 14.000	100-97-0,108-95-2
Fiberglass	3.000- 6.000	
OTHER		
Not Applicable		

#### SECTION 3. HAZARDS IDENTIFICATION

##### INHALATION ACUTE EXPOSURE EFFECTS

Dust may be slightly irritating to eyes and respiratory tract at high concentrations.

##### INHALATION CHRONIC EXPOSURE EFFECTS

Chronic: May affect breathing capacity.

For products containing phenol/formaldehyde resin, dust generated from intended use may contain trace amounts of phenol and formaldehyde which under excessive exposure may cause skin sensitization and airway obstruction.

For products containing inorganic fluorides:

Excessive exposure to inorganic fluorides have been shown to increase bone density.

##### EYE CONTACT ACUTE EXPOSURE EFFECTS

Dust may irritate eyes.

**SKIN CONTACT ACUTE EXPOSURE EFFECTS**

Some may experience skin irritation from dust.

**INGESTION ACUTE EXPOSURE EFFECTS**

No known adverse effects, but ingestion not recommended.

**SECTION 4. FIRST AID MEASURES**

**INHALATION**

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately .

**SKIN CONTACT**

Wash affected areas with soap and water. Obtain medical assistance.

**EYE CONTACT**

Wash with large amounts of water. Obtain first aid and medical assistance, if needed.

**INGESTION**

Call poison control center, hospital emergency room or physician immediately.

**SECTION 5. FIRE FIGHTING MEASURES**

**FIRE FIGHTING PROCEDURES**

Not Applicable

**HAZARDOUS PRODUCTS/COMBUSTION**

None.

**HAZARD RATING SOURCE**

NFPA

HEALTH

1

FLAMMABILITY

0

REACTIVITY

0

OTHER

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**CLEAN-UP**

Follow normal clean up procedures.

## **SECTION 7. HANDLING AND STORAGE**

### **HANDLING**

- Always HANDLE AND STORE wheels in a CAREFUL manner.
- Always VISUALLY INSPECT all wheels before mounting.
- Always CHECK MACHINE SPEED against the established maximum safe operating speed MARKED ON THE WHEEL.
- Always CHECK MOUNTING FLANGES for equal and correct diameter.
- Always USE MOUNTING BLOTTERS.
- Always be sure WORK REST is properly adjusted.
- Always USE A SAFETY GUARD covering at least one-half of the grinding wheel.
- Always allow NEWLY MOUNTED WHEELS to run at operating speed, with guard in place, for at least one minute before grinding.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **VENTILATION PROTECTION**

Recommend using local exhaust ventilation when general ventilation is not keeping the airborne concentration below the TLV.

### **RESPIRATORY PROTECTION**

Respirators are required when airborne contaminant levels exceed the TLV(s).

### **EYE PROTECTION**

Always WEAR SAFETY GLASSES or some type of eye protection when grinding.

### **OTHER PROTECTION**

Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

### **APPEARANCE & ODOR**

Solid article. Odorless.

## **SECTION 10. STABILITY AND REACTIVITY**

### **INCOMPATIBILITIES**

Avoid acids of all types with a pH < 4.0.

### **DECOMPOSITION**

In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the grinding wheel components

For products containing Phenol and formaldehyde resin, thermal decomposition may produce trace amounts of phenol and formaldehyde.

For products containing inorganic fluorides, thermal decomposition may produce trace amounts of fluorides.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

### CARCINOGENICITY

This product or its ingredients have not been identified as a carcinogen or probable carcinogen by NTP, IARC monographs, or OSHA. LD50/LC50  
Values are not appropriate or available.

## **SECTION 12. ECOLOGICAL INFORMATION**

### CHEMICAL FATE

Resin bonded materials demonstrate similar degradation rates as Phenolic plastics.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

### WASTE DISPOSAL

Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

## **SECTION 14. TRANSPORT INFORMATION**

### HAZARD CLASS

This product is not hazardous as defined by the Department of Transportation. (USA)

This product is "Not Regulated" under the Transportation of Dangerous Goods Act. (CAN)

## SECTION 15. REGULATORY INFORMATION

### EXPOSURE LIMITS/REGULATORY INFORMATION

SUBSTANCE DESCRIPTION	UNITS	OSHA	ACGIH	MOL
Aluminum Oxide, Non-fibrous	MG/M3	15.0000	10.0000	10.0000
Cured Phenol Formaldehyde Resin	PPM	0.0000	0.0000	0.0000
Fiberglass	FBR/CC	1.0000	0.0000	0.0000

#### LEGEND :

##### EXPOSURE LIMIT DESCRIPTIONS

CA PROP 65

Not Applicable

TSCA

Section 8(b) - Inventory Status

All components of this product are registered under the regulations of the Toxic Substance Control Act.

##### DOMESTIC SUBSTANCE LIST

All components of this product are found on the Domestic Substance List.

## SECTION 16. OTHER INFORMATION

#### DISCLAIMER

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof; however, the Company makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.